

REFRIGERANT R417A

Page: 1

Compilation date: 28/05/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: REFRIGERANT R417A

Product code: R417A

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Star International Ltd

Star Hosue, Turbine Business Park

Turbine Road, Birkenhead, Merseyside CH41 9BA

United Kingdom

Tel: +44 (0) 1244 504 500

Email: enquiries@Star-international.co.uk **Web:** www.star-international.co.uk

1.4. Emergency telephone number

Emergency tel: Carechem24 +44 (0)1865 407333

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Press. Gas: H280

Most important adverse effects: Contains gas under pressure; may explode if heated.

2.2. Label elements

Label elements:

Hazard statements: H280: Contains gas under pressure; may explode if heated.

Hazard pictograms: GHS04: Gas cylinder



Signal words: Warning

Precautionary statements: P410+403: Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.



REFRIGERANT R417A

Page: 2

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

REFRIGERANT R134A - REACH registered number(s): 01-2119459374-33

EINECS	CAS	PBT / WEL	CLP Classification	Percent
212-377-0		Substance with a Community workplace exposure limit.	Press. Gas: H280	30-50%

PENTAFLUOROETHANE - REACH registered number(s): 01-2119485636-25

206-557-8	354-33-6	Substance with a Community	Press. Gas: H280	30-50%
		workplace exposure limit.		

BUTANE

203-448-7	106-97-8	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	1-10%
		workplace exposure limit.		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Do not

use hot water. If frostbite has occurred call a physician.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Not applicable.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious,

check for breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be redness or whiteness of the skin in the area of exposure. Frost-bite may occur

causing the affected area to become white and numb.

Eye contact: There may be severe pain. Corneal burns may occur. May cause permanent damage.

Ingestion: There may be irritation of the throat.

Inhalation: Inhalation may produce the following symptoms: Shortness of breath, dizziness, weakness,

nausea, headache, narcosis, irregular cardiac activity. Asphyxia. May cause cardiac

arrhythmia.

Delayed / immediate effects: May cause cardiac arrhythmia.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures



REFRIGERANT R417A

Page: 3

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Suitable

extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Non flamable gas.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade

immediately. If outside keep bystanders upwind and away from danger point.

6.2. Environmental precautions

Environmental precautions: Stop release if safe to do so. Prevent from entering sewers, basements and work pits, or any

place where the accumulation can be dangerous.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Material evaporates. Ventilate the area, especially low or enclosed places where heavy

vapours might collect.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the

air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Store at a temperature not

exceeding 45°C.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection



REFRIGERANT R417A

Page: 4

8.1. Control parameters

Hazardous ingredients:

REFRIGERANT R134A

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	4240 mg/m3	-	-	-

PENTAFLUOROETHANE

EU	1000 ppm	-	-	-
----	----------	---	---	---

BUTANE

UK	1450 mg/m3	1810 mg/m3	-	-

DNEL/PNEC Values

Hazardous ingredients:

REFRIGERANT R134A

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	2476 mg/m3	Workers	Systemic
DNEL	Inhalation	2476 mg/m3	Consumers	Systemic
PNEC	Fresh water	0.01 mg/l	-	-
PNEC	Marine water	0.75 mg/l	-	-
PNEC	Microorganisms in sewage treatment	73 mg/l	-	-

PENTAFLUOROETHANE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	16444 mg/m3	Workers	Systemic
DNEL	Inhalation	1753 mg/m3	Consumers	Systemic
PNEC	Fresh water	0.1 mg/l	-	-
PNEC	Fresh water sediments	0.6 mg/kg	-	-1

8.2. Exposure controls

 $\label{lem:engineering measures:} \textbf{Ensure there is sufficient ventilation of the area.}$

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Vapours are

heavier than air and can cause suffocation by reducing the oxygen available for breathing.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields. Safety goggles. Face-shield. Safety glasses.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties



REFRIGERANT R417A

Page: 5

9.1. Information on basic physical and chemical properties

State: Liquified gas

Colour: Colourless

Odour: Characteristic odour

Boiling point/range°C: -39.1

Flammability limits %: lower: None

Flash point°C: Not applicable.

upper: None
Vapour pressure: 9.835 Bar at 25oC

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

REFRIGERANT R134A

GASES	RAT	4H LC50	567000	ppmV		
-------	-----	---------	--------	------	--	--

PENTAFLUOROETHANE

GASES	RAT	4H LC50	800000	Vmqq
OAOLO	13/5 1	TI LO30	000000	ppiliv

Toxicity values: No data available.



REFRIGERANT R417A

Page: 6

Symptoms / routes of exposure

Skin contact: There may be redness or whiteness of the skin in the area of exposure. Frost-bite may occur

causing the affected area to become white and numb.

Eye contact: There may be severe pain. Corneal burns may occur. May cause permanent damage.

Ingestion: There may be irritation of the throat.

Inhalation: Inhalation may produce the following symptoms: Shortness of breath, dizziness, weakness,

nausea, headache, narcosis, irregular cardiac activity. Asphyxia. May cause cardiac

arrhythmia.

Delayed / immediate effects: May cause cardiac arrhythmia.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

REFRIGERANT R134A

ALGAE	72H ErC50	118	mg/l
Daphnia magna	48H EC50	980	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	450	mg/l

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Ozone Depletion Potential (ODP): 0 (R11 = 1) R417A Global Warming Potential (GWP): 2346

(CO2=1) Contains fluoronated greenhouse gases covered by the Kyoto Protocol.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Product evaporates.

Recovery operations: Consult manufacturer or supplier for information regarding recovery and recycling of the

product. If recovery is not possible, incinerate at a licenced instalation.

Waste code number: 14 06 01

Disposal of packaging: Return to supplier.



REFRIGERANT R417A

Page: 7

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1078

14.2. UN proper shipping name

Shipping name: REFRIGERANT GAS, N.O.S.

(NORFLUANE; PENTAFLUOROETHANE)

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: C/E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Contains fluorinated greenhouse gases covered by the Kyoto Protocol.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H280: Contains gas under pressure; may explode if heated.

Legal disclaimer: National Refrigerants Ltd believes that the information and recommendations contained

herein (including data and statments) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY,

OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE

INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated. National Refrigerants expressly disclaims any and all liability as

to any results obtained or arising from any use of the product or reliance on such information.

[final page]