

MGO ANTIGEL DATA SHEET

STAR MARINER MGO ANTIGEL

PRODUCT CODES: 20 Ltr: 00920043 / 205 Ltr: 00920036

DESCRIPTION

MGO ANTIGEL is a Marine Diesel fuel antiwaxing / antigel additive , formulated to counteract fuel waxing /gelling , when exposed to extreme cold winter conditions.

APPLICATION

MGO ANTIGEL is a preventative maintenance product which should be applied to storage tanks , before fuel is due to be exposed to cold winter conditions.

MGO ANTIGEL should be applied to the main fuel storage tanks prior to tanks being refilled , to ensure product is completely absorbed into the fuel.

MGO ANTIGEL mixes easily with the fuel.

FUEL DOSAGE

When dosing Winter grade Diesel fuels , the recommended dose rate is : 1 litre of MGO ANTIGEL to 1,000 (1 cu. metre) of fuel.

Should Winter grade Diesel Fuel be mixed with Summer grade fuel (both possessing differing CFPPs) , a stronger dose is recommended...e.g. 1 litre of MGO ANTIGEL to 750 litres (0.75 cu.meter) of fuel.

BENEFITS

Winter grade MGO treated with MGO ANTIGEL will achieve optimum cold flow properties (CFPP) of (down to) -24 degrees Centigrade.

Final CFPP figure may vary , as it is based on the MGO's CFPP prior to treatment.

Read the Material Safety Data Sheet before using this product.

For detailed information on safety and health, please refer to Material Safety Data and/or Product Label